


## TECHNICAL DATA SHEET

# SC 5030



Komplet's track mounted screener SC5030, is a lightweight and compact self-propelled screening machine. Easy to handle and easy to transport, it's designed to perform for intense daily screening activity or for pre-screening prior to crushing operations.

STANDARD FEATURES
<ul style="list-style-type: none"> <li>• Autec remote control for undercarriage movements</li> <li>• Screening grizzly bars</li> </ul>
ACCESSORIES
<ul style="list-style-type: none"> <li>• Remote control for all movements</li> <li>• Dust control system</li> <li>• Screening grid made in metal sheet</li> <li>• Screening grid made in metallic net</li> </ul>

ISUZU ENGINE		
Power	kW / Hp	32 / 43.5
Consumption	Gal / h	2.25
PERFORMANCE*		
Production	T / h	50 - 350
Max Size	in.	24
Standard Weight	lbs	26,456
*The production performance is dependent on the type and volume of material being processed as well as the size of the material produced.		
WEIGHTS & DIMENSIONS		
MACHINE	Operation	Transport
Length (ft & in)	32' 5"	32' 5"
Width (ft & in)	35' 5"	7' 5"
Height (ft & in)	7' 11"	8' 3"
RUBBER TRACKS		
Length	ft & in	9' 1"
Width	ft & in	1' 4"
VIBRATING LOADING HOPPER		
Dimension grid	ft & in	8' 3" x 3' 4"
Screening grid	Qty	2
FEEDING BELT		
Length	ft & in	8' 3"
Width	ft & in	2' 8"
Hopper capacity	yd <sup>3</sup>	3.3
Loading Height	ft & in	8' 7"
FINE MATERIAL BELT		
Length	ft & in	20' 9"
Width	ft & in	2'
Discharge Height	ft & in	9' 3"
MEDIUM MATERIAL BELT		
Length	ft & in	20' 9"
Width	ft & in	2'
Discharge Height	ft & in	9' 3"
OVERSIZE MATERIAL BELT**		
Length	ft & in	12' 2"
Width	ft & in	2' 8"
Discharge Height	ft & in	7'
2 <sup>nd</sup> Discharge Height**	ft & in	8'
**When needed can be used for just 2 selections lowering the oversize belt.		