



**K-JC 503**

**TECHNICAL SPECIFICATION**



# K-JC 503

The KJC503 is our most compact mobile jaw crusher, providing an ideal solution for construction companies and contractors who want to recycle their construction and demolition waste onsite. Equipped by tracks and radio remote control, they directly reutilize the CRUSHED material, avoiding transport costs.

1. CRUSHER
2. FEEDER
3. PRODUCT CONVEYOR
4. POWERUNIT
5. TRACKS



# CRUSHER





# TECHNICAL DATA

## JAW CRUSHER

**Crusher dimension**  
480x250 mm

**Jaw adjustment**  
Hydraulic

**Granulometry**  
15-80 mm

## FEEDING: LOADING BELT WITH HOPPER

**Length**  
1780 mm

**Width**  
1280 mm

**Hopper Capacity**  
0,6 m<sup>3</sup>

**Loading Height**  
1900 mm

## EXTRACTING BELT

**Length**  
2500 mm

**Width**  
400 mm

**Pile height**  
1100 mm

## ISUZU ENGINE

**Power**  
21\28,5 kW/Hp

**Consumption**  
5,5 L/h

**Cylinder**  
N°3

**Cooling**  
Water

## RUBBER CRAWLED TRACK

**Length**  
2100 mm

**Width**  
300 mm

## PERFORMANCE

**Production**  
5-30 T/h

**Max size**  
80 mm

**Standard weight**  
3400 kg





**STANDARD MACHINE**  
Remote control for all the movements.

**ACCESSORIES**

- Magnetic roller.
- Dust dumping system.
- Side protection kit.



# TRANSPORT DIMENSION & WORKING DIMENSION





