



KROKODILE
TECHNICAL SPECIFICATION

KROKODILE

Flexible, powerful, economical. Our KROKODILE gives you all the advantages of mobile shredding while being extremely compact. This all-rounder shreds even difficult materials with its robust design and powerful engine.

1. SHREDDER UNIT
2. FEEDER
3. POWERUNIT
4. PRODUCT CONVEYOR
5. TRACK/ CHASSIS





TECHNICAL DATA

SHREDDING UNIT

Shafts dimension
4.9 ft
Shafts diameter
2.2 ft

Rotation speed
0-40 Rpm

Css range
3-1/4 in to 5-3/4 in

HOPPER AREA

VOLUME
2,3m³

FOLDING PRODUCT CONVEYOR

Width 2.6 ft
Hydraulic folding
system by 2 cylinder

POWERUNIT

Power
T3 160kw/220hp
diesel engine
T4f 160kw/220hp
diesel engine

Cylinder
N°4

Cooling
Water

CRAWLED TRACK

And skip hook system
in the same machine

PERFORMANCE

Production
Up to 200 tph

Standard weight
29,763 lbs



STANDARD MACHINE

- Doglead remote control
- Easy 2 use control panel
- Monitoring and remote access to machine
- Gps geolocation
- Hydraulic cylinder to open side walls
- Quick and fast shafts change system

ACCESSORIES

- Shafts for wood & plastic
- Overband magnetic
- Rear tilt hopper
- Remote control to drive undercarriage/ rear hopper
- Spraybar
- Antidustsystem



TRANSPORT DIMENSION & WORKING DIMENSION



