



**K-JC 704**

**TECHNICAL SPECIFICATION**



# K-JC 704

The KJC704 has been specifically designed for operators for whom versatility, maneuverability and transportability are of key importance. It is small enough to fit inside a container for transport but strong enough to withstand the toughest of applications. The KJC704 features a '680mm x 400mm' single toggle Jaw Crusher that can be adjusted hydraulically THE css -

- 1. CRUSHER
- 2. FEEDER
- 3. PRODUCT CONVEYOR
- 4. POWERUNIT
- 5. CONTROL SYSTEM
- 6. TRACKS







# TECHNICAL DATA

## JAW CRUSHER

**Crusher dimension**  
27 in x 16 in

**Jaw adjustment**  
700x400 Hydraulic

**Granulometry**  
3/4 in - 3 1/4 in

## FEEDING: GRIZZLY WITH HOPPER

**Length**  
7.9 ft

**Width**  
5.1 ft

**Hopper Capacity**  
2,3 m<sup>3</sup>

**Loading Height**  
8.8 ft

## FOLDING EXTRACTING BELT

**Length**  
20.8 ft

**Width**  
2.6 ft

**Pile height**  
5.9 ft

## EXTRACTING BELT OF FINE MATERIAL PLACED UNDER THE GRIZZLY

**Length**  
5.5 ft

**Width**  
1.3 ft

**Pile height**  
6.1 ft

## ISUZU TURBO ENGINE

**Power**  
74 Hp

**Consumption**  
3.2 g/h

**Cylinder**  
N°4

**Cooling**  
Water

## CRAWLED TRACK WITH PADS

**Length**  
9 ft

**Width**  
1.3 ft

**Speed**  
1° 0,7 km\h  
2° 2,2 km\h

## PERFORMANCE

**Production**  
90 T/h

**Max size**  
1.9 ft

**Standard weight**  
26,455 lbs





### STANDARD MACHINE

- Remote control for all the movements.
- Reversible belt fine material.
- Ladder to inspect the crusher.
- Side protection.

### ACCESSORIES

- Magnetic belt.
- Dust dumping system.

### TRANSPORT DIMENSION

Length 5600 mm  
Width 2250 mm  
Height 2690 mm



# TRANSPORT DIMENSION & WORKING DIMENSION





